

HTTP-Based Platforms

| Platform | Origin | Type | URL |
|---------------------------------|-------------------------------|--|--|
| ADN, HTTP Large, and HTTP Small | CDN Origin or Customer Origin | SSL Traffic – Hosted SAN & Custom SSL Certificates | Edge CNAME URL An edge CNAME configuration must be created for each domain referenced by an SSL certificate installed on your behalf. |
| ADN | Customer Origin | Standard | http://adn.xxx.<Domain>/80xxx/<Customer Origin>/ |
| ADN | CDN Origin | Standard | http://adn.xxx.<Domain>/00xxx/ |
| HTTP Large | Customer Origin | Standard | http://wpc.xxx.<Domain>/80xxx/<Customer Origin>/ |
| HTTP Large | CDN Origin | Standard | http://wpc.xxx.<Domain>/00xxx/ |
| HTTP Small | Customer Origin | Standard | http://wac.xxx.<Domain>/80xxx/<Customer Origin>/ |
| HTTP Small | CDN Origin | Standard | http://wac.xxx.<Domain>/00xxx/ |

Token-Based Authentication

DIRECTORY COMPARISON

| | | | |
|---------------------------------|-----------------|----------|--|
| ADN, HTTP Large, and HTTP Small | Customer Origin | Standard | CDN URL http://<Domain>/80xxx |
| ADN, HTTP Large, and HTTP Small | Customer Origin | Standard | Edge CNAME URL http://<Domain>/80xxx (Comparison occurs after our edge servers rewrite the edge CNAME URL to a CDN URL.) |
| ADN, HTTP Large, and HTTP Small | CDN Origin | Standard | CDN URL http://<Domain>/00xxx |
| ADN, HTTP Large, and HTTP Small | CDN Origin | Standard | Edge CNAME URL http://<Domain> https://<Domain> |

REQUEST

| | | | |
|---------------------------------|-------------------------------|------------------------|---------------------------------|
| ADN, HTTP Large, and HTTP Small | CDN Origin or Customer Origin | Standard & SSL Traffic | <File Name>.<Extension>?<Token> |
|---------------------------------|-------------------------------|------------------------|---------------------------------|

Primary and Backup Key

Take the following precautions to secure the primary and backup key:

- Ensure that these keys are never shared outside of your organization.
- Periodically rotate the primary key.
- Remove the backup key upon transitioning to a new primary key.

Authentication Directory Configuration

- Specify a relative path that starts with a forward slash (/).
- Add the root folder (/) as an authentication directory to require authentication for all requests on the current platform.
- The comparison of an authentication directory to a request starts after the base URL. The above table indicates this starting point.